

## C T 1.3 L S

SIZES_	XS (43cm), S (47cm), M (52cm), L (56cm)
COLOR(S)_	Metallic khaki
FRAME_	BESV CT 1. Series alloy frame, Shimano Steps and internal battery compatible
DRIVE UNIT_	Shimano EP600 center-motor, 250W rated power, 85Nm of torque, 25km/h maximum assist
BATTERY_	630Wh integrated Lithium Ion battery, approved for Shimano Service Program, with Smart 4-5.6A charger
DISPLAY_	Shimano SC-E5003, left hand mounted, with LCD display
FORK_	SR Suntour MobieA32, Lockout, Coil damping, tapered alloy steerer, travel 75mm, Thru-axle
CRANKSET_	Chainring: Gates CDX Spider 42T with chainguard / Crank arm: Samox for Shimano Steps
BOTTOM BRACKET_	Shimano, integrated in motor
PEDALS_	Wellgo pedals with reflectors
REAR DERAILLEUR_	Enviolo Trekking, 380% gear ratio
SHIFTERS_	Enviolo manual
CASSETTE_	Gates CDX rear sprocket / 24T / Enviolo 44T spline
CHAIN_	Gates CDX belt / 122T
WHEELSET_	Formula CL-71 front hub, Enviolo Trekking 380% gear ratio rear hub, 700c multichamber alloy rims 36H
TIRES_	MaxxisMetropass, 700x50c, Silkworm, 60TPIwirebeadwithpunctureprotection, withreflectivestripe
BRAKESET_	Shimano MT410, 2-piston hydraulic disc, with 180mm front and rear rotors
BRAKE LEVERS_	Shimano MT402, 3 finger lever
HEADSET_	Acros, AZX-585, 1.5" headset, angular contact bearings, integrated cable routing
HANDLEBAR_	Alloy City-Trekking rise bar, 6066 alloy, 40mm rise, sweep: 20 degree up, 31.8mm clamp
STEM_	3D Forged alloy City-Trekking stem, SP-Connect mount, adjustable 0-90 degree, 31.8mm clamp
GRIPS_	Comfortable gel grips with padding
SADDLE_	Selle Italia S5 Superflow
SEATPOST_	Suspension seatpost with anty-sideplay, 40mm travel, 31.6mm diameter, 12mm offset
FENDERS_	Alloy extruded fenders, front & rear 3/4 length, stainless steel hardware
HEADLIGHT_	Lezyne eBike Power E115, 6-12v, 115 lux, with reflector

REAR CARRIER\_ Tubular aluminium carrier, with Snapit platform and spring clamp, H-Cargo rear light mount

 ${\tt TAILLIGHT\_} \quad {\tt Herrmans\,H-Cargo,\,6-12v,\,with\,reflector}$ 

ACCESSORIES\_ Adjustable kickstand

380° GEAR RATIO

75

SUSPENSION TRAVEL

85<sup>NM</sup>
TORQUE

630<sup>wh</sup>

## E-SYSTEM

\_Powerful Shimano EP600 motor with long lasting Darfon 630Wh battery

## TIRES

\_On the safe side with the Maxxis Metropass.

## BELT DRIVE

\_Long lasting and maintenance-free Gates CDX belt drive