

TR 1.2 LS

SIZES_ XS (43cm), S (47cm), M (52cm), L (56cm)

(S)_	Metallic blue
1E_	BESV TR 1.Series alloy frame, Shimano Steps and internal battery compatible
IIT_	Shimano EP600 center-motor, 250W rated power, 85Nm of torque, 25km/h maximum assist
/ _	630Wh integrated Lithium Ion battery, approved for Shimano Service Program, with Smart 4-5.6A charger
	Shimano SC-E5003, left hand mounted, with LCD display
	SR Suntour Mobie25, Lockout, Air damping, tapered alloy steerer, travel 75mm, Thru-axle
	Samox for Shimano Steps, 38T chainring
	Shimano, integrated in motor
	Wellgo pedals with reflectors
	Microshift XLE 11, 11 speed
	Microshift XLE 11, 11 speed
	Microshift XLE 11, 11 speed, 11-42T
	KMC e11Turbo, with Quick-Link
	Shimano HB-MT400 front hub, Formula CL-3248 rear hub, 700c multichamber alloy rims 36H
1	Maxxis Metropass, 700x50c, Silkworm, 60 TPI wire bead with puncture protection, with reflective stripe
	Shimano MT410, 2-piston hydraulic disc, with 180mm front and rear rotors
	Shimano MT402, 3 finger lever
,	Acros, AZX-585, 1.5" headset, angular contact bearings, integrated cable routing
	Alloy City-Trekking rise bar, 6066 alloy, 40mm rise, sweep: 20 degree up, 31.8mm clamp
	3D Forged alloy Trekking stem, adjustable 0-90 degree, 31.8mm clamp
	Comfortable gel grips with padding
	Selle Italia S5 Superflow
	Promax SP-726, 31.6mm diameter
	Alloy extruded fenders, front & rear 3/4 length, stainless steel hardware
	Lezyne eBike Power E115, 6-12v, 115 lux, with reflector
	Herrmans H-Cargo, 6-12v, with reflector
-	Tubular aluminium carrier, with Snapit platform and spring clamp, H-Cargo rear light mount

11 75 FORK TRAVEL



E-SYSTEM

_Powerful Shimano EP600 motor with long lasting Darfon 630Wh battery.

TIRES

_On the safe side with the Maxxis Metropass.

SUSPENSION

_Comfort and trackion thanks to Suntour Mobie Air front fork.