



TRX 1.5

| | |
|------------------|---|
| SIZES_ | XS (43cm), S (47cm), M (52cm), L (56cm) |
| COLOR(S)_ | Steel grey with night black |
| FRAME_ | Hard-tail BESV TRX Series alloy frame, Shimano Steps and internal battery compatible |
| DRIVE UNIT_ | Shimano EP600 center-motor, 250W rated power, 85Nm of torque, 25km/h maximum assist |
| BATTERY_ | 504Wh integrated Lithium Ion battery, approved for Shimano Service Program, with Smart 2A charger |
| DISPLAY_ | Shimano SC-E5003, left hand mounted, with LCD display |
| FORK_ | SR Suntour XCM34, 34mm stanchions, Lockout, Coil damping, 1.1/8"-1.5" tapered alloy steerer, 120mm travel |
| CRANKSET_ | Samox for Shimano Steps, 34T chainring |
| BOTTOM BRACKET_ | Shimano, integrated in motor |
| PEDALS_ | Wellgo, alloy body, ball bearings |
| REAR DERAILLEUR_ | Microshift XLE, 10 speed |
| SHIFTERS_ | Microshift XLE, 10 speed |
| CASSETTE_ | Microshift XLE, 10 speed, 11-42T |
| CHAIN_ | KMC e10Turbo, with Quick-Link |
| WHEELSET_ | Formula CL-811 front hub, Formula CL-3248 rear hub, Boost hubs spacing, WTB STi27 29" multichamber alloy rims 32H |
| TIRES_ | Maxxis Ardent, 29"x2.4", Normal Compound, EXO, 60 TPI foldable |
| BRAKES_ | Hydraulic disc brake, 2-piston, 180mm front and rear rotors |
| BRAKE LEVERS_ | 2 finger hydraulic disc brake lever |
| HEADSET_ | Acros, AZX-581, 1.5" headset, angular contact bearings, integrated cable routing |
| HANDLEBAR_ | E-MTB reis bar, 6066 alloy, 4mm rise, sweep: 7 degree back, 31.8mm clamp |
| STEM_ | E-MTB 3D Forged alloy stem, 31.8mm clamp, for internal cable routing |
| GRIPS_ | E-MTB gel grips with padding and BESV clamp |
| SADDLE_ | Selle Italia X3 eBike |
| SEATPOST_ | Promax SP-726, 31.6mm diameter |

10
SPEED

120^{MM}
SUSPENSION
TRAVEL

85^{Nm}
TORQUE

504^{WH}
BATTERY

MOTOR

_Big torque momentum of EP600 engine will boost up your ride.

TIRES

_Great grip and low rolling resistance of Maxxis Ardent.

BRAKES

_Hydraulic disc brake with 180mm rotors.