



CT - B 1.1

SIZES_	S (47cm), M (52cm), L (56cm), XL (60cm)
COLOR_	Metallic steel with black gloss
FRAME_	BESV CT-B 1.Series full smooth welded alloy frame, Bosch motor and internal battery compatible
DRIVE UNIT_	Bosch Performance line center-motor, 250W rated power, 75Nm of torque, 25km/h maximum assist
BATTERY_	625 Wh Bosch Power Tube, with 4A charger
LOCK_	Abus battery key-lock and Abus 4650XL rear wheel lock
DISPLAY_	Bosch Intuvia with LED display and Bluetooth connectivity
FORK_	SR Suntour MobieA32, Lockout, Coil damping, tapered alloy steerer, travel 75mm, Thru-axe
CRANKSET_	Chainring: Gates CDX Spider 48T / Crank arm: Samox for Bosch
BOTTOM BRACKET_	Bosch, integrated in motor
PEDALS_	Wellgo pedals with reflectors
REAR DERAILLEUR_	Enviolo Trekking, 380% gear ratio
SHIFTERS_	Enviolo manual
CASSETTE_	Gates CDX rear sprocket / 24T / Enviolo 44T spline
CHAIN_	Gates CDX belt / 128T
WHEELSET_	Shimano HB-TC500-15 front hub, Enviolo Trekking 380% gear ratio rear hub, 700c multichamber alloy rims 36H
TIRES_	Schwalbe Energizer Plus, 50x622, Addix E, Twin Skin, 67 TPI wire bead with Green Guard protection, reflective stripe
BRAKESET_	Shimano MT410, 2-piston hydraulic disc, with 180mm front and rear rotor
BRAKE LEVERS_	Shimano MT402, 3 finger lever
HEADSET_	Acros, AZX-585, 1.5" headset, angular contact bearings, integrated cable routing
HANDLEBAR_	All alloy City-Trekking rise bar, 6066 alloy, 40mm rise, sweep: 20° up, 31.8mm clamp
STEM_	3D Forged alloy City-Trekking stem, SP-Connect mount, adjustable 0-90°, 31.8mm clamp
GRIPS_	Comfortable gel grips with padding
SADDLE_	Selle Italia Max S5 Superflow
SEATPOST_	Suspension seatpost with anty-sideplay, 40mm travel, 31.6mm diameter, 12mm offset
FENDERS_	Alloy extruded fenders, front & rear 3/4 length, stainless steel hardware
HEADLIGHT_	Lezyne e-bike Mini E65, 6-12V, 65 Lux, with reflector
TAILLIGHT_	Herrmans H-Cargo, 6-12V, with reflector
REAR CARRIER_	Tubular aluminium carrier, with MIK HD platform and spring clamp, H-Cargo rear light mount
ACCESSORIES_	Adjustable kickstand, Chainguard

380%
GEAR RATIO

75^{MM}
SUSPENSION
TRAVEL

75^{NM}
TORQUE

625^{WH}
BATTERY

E - SYSTEM

_Smooth and fast ride with the Bosch Performance motor matched with the Bosch Powertube 625Wh battery. Compatible with the Bosch Smart System.

CARRIER

_With the MIK HD platform you can attach many bags, accessories or even a child seat to the carrier platform.

GEARING

_Always in the right gear thanks to the Enviolo 380 inner gear hub.