

## TRX-B1.3

| SIZES_           | S (42.5cm), M (46cm), L (49cm)  |
|------------------|---|
| COLOR_           | Intense red with black satin  |
| FRAME_           | Hard-tail BESV TRX-B Series smooth welded alloy frame, Bosch motor and internal battery compatible                        |
| DRIVE UNIT_      | Bosch Performance CX center-motor, 250W rated power, 85Nm of torque, 25km/h maximum assist                                |
| BATTERY_         | Bosch Power Tube 625 Wh, with 4A charger  |
| LOCK_            | Abus battery key-lock   |
| DISPLAY_         | Bosch Kiox with LED display and Bluetooth connectivity  |
| FORK_            | Rock Shox Judy Silver TK, 32mm stanchions, Solo Air, 1 1/8"-1.5" tapered alloy steerer, travel 120mm,<br>Maxle Stealth    |
| CRANKSET_        | Samox for Bosch, 34T chainring  |
| BOTTOM BRACKET_  | Bosch, integrated in motor  |
| PEDALS_          | Wellgo, alloy body, ball bearings   |
| REAR DERAILLEUR_ | Shimano Deore RD-M6100, 12 speed  |
| SHIFTERS_        | Shimano Deore SL-M6100, 12 speed  |
| CASSETTE_        | Shimano Deore CS-M6100, 12 speed, 10-51T  |
| CHAIN_           | KMC e12Turbo, with Quick-Link   |
| WHEELSET_        | Shimano HB-TC500-15-B front hub and FH-TC500-MS-B rear hub, Boost hubs spacing, WTB STi27 29" multichamber alloy rims 32H |
| TIRES_           | Schwalbe Smart Sam, 29×2.6", 65×622, Performance Line, Addix, 67 TPI wire bead, Tanwall sides                             |
| BRAKESET_        | Shimano MT200, 2-piston hydraulic disc, with 180mm front and rear rotor   |
| BRAKE LEVERS_    | Shimano MT201, 2 finger lever   |
| HEADSET_         | Acros, AZX-581, 1.5" headset, angular contact bearings, integrated cable routing  |
| HANDLEBAR_       | E-MTB rizer bar, 6066 alloy, 4mm rise, sweep: 7° back, 31.8mm clamp   |
| STEM_            | E-MTB 3D Forged alloy stem, 31.8mm clamp, for internal cable routing  |
| GRIPS_           | E-MTB gel grips with padding and BESV clamp   |
| SADDLE_          | Selle Italia S5 Superflow   |
| SEATPOST_        | Promax SP-726, 31.6mm diameter  |

12 SPEED 120 MM SUSPENSION TRAVEL

85<sup>Nm</sup>
TORQUE

625<sup>wh</sup>
BATTERY

## FRAME

\_Newly developed alloy frame for Bosch system. Smooth integration of components blended with great geometry.

## DRIVETRAIN

\_ High-performance, 12-speed, Shimano Deore drivetrain with wide range gear combo in rear cassette 10-51 teeth.

## TIRES

\_Supreme handling and control in any conditions with Schwalbe Smart Sam tires.