SPECIFICATION

CT 2.1



Frame BESV premium alloy frame with down tube for integrated Darfon battery, Shimano center-motor with protection cover, tapered 1 1/8" - 1.5" head tube, post disc mount, cold-forged dropout and replaceable hanger for Shimano Inner Gear hubs Drive Unit Shimano E-6110 center-motor, 250W rated power, 60Nm of torque_2Skm/h maximum assist, for coaster-brake Darfon 504Wh, intergrated battery, approved for 'Shimano Service Program', with Smart 2A charger Display Shimano SC-E6100 center mounted LCD display with Bluetooth and ANT private connectivity Fork RST Volant, Lockout, Coil damping, Lapered alloy steerer, travel 50mm, QR-axle Statery Shimano, integrated in motor Vedals Wellog pedals with reflectors Rear Derailleur Shimano Nexus 8 speed Shimano Inner Gear sprocket, 20T Shimano Inner Gear sprocket, 20T Chain KMC E101 EPT Shimano MT200, 2-piston hydraulic disc, with 180mm front and 160mm rear rotors Stake Levers Shimano MT200, 2-piston hydraulic disc, With 180mm front and 160mm rear rotors Stake Levers Shimano MT200, 2-piston hydraulic disc, with 180mm front and 160mm rear rotors Stake Levers Shimano MT200, 2-piston hydraulic disc, with 180mm front and 160mm rear rotors Stake Levers Shimano MT200 Shimano MT201 Shimano Sete ang 60	Sizes	Lady: S (45cm), M (50cm), L (55cm)
head tube, post disc mount, cold-forged dropout and replaceable hange for Shimano Iner Gear hubsDrive UnitShimano E-6110 center mount, 250W rated power, 60Nm of torque, 25km/h maximum assist, for coaster-brakeDarfon 50-40Wb, intergrated battery, approved for 'Shimano Service Program, with Smart 2A chargerDisplayShimano SC-E6100 center mounted LCD display with Bluetooth and ANT private connectivityForkRST Volant, Lockout, Coll damping, tapered alloy steerer, travel 50mm, QR-axleForksetSamox for Shimano Steps, 38T chainringbottom BracketShimano Integrated in motorVedlayWellgo pedlas with reflectorsRear DerailleurShimano Nexus 8 speedShimano Nexus 8 speedCassetteShimano Nexus 8 speedCharlenKMC E101 EPTWheelsetShimano NB-TXS05 front hub, Shimano Nexus 8 speed rear hub, for Center Lock disc and coaster-brake brakes, CN streight stainless steelspokes, SR J23ZK 700c multichamber alloy rims for disc brakes with 36HKrikesetShimano ME-7XS05 front hub, Shimano Nexus 8 speed rear hub, for Center Lock disc and coaster-brake brakes, CN streight stainless steelspokes, SR J23ZK 700c multichamber alloy rims for disc brakes with 36HKrikesetShimano ME-7XS05 front hub, Shimano Nexus 8 speed rear hub, for Center Lock disc and coaster-brake brakes, CN streight stainless steelspokes, SR J23ZK 700c multichamber alloy rims for disc brakes with 36HKrikesetShimano MT200, 2-piston hydraulic disc, with 180mm front and 160mm rear rotorsStakesetShimano MI200Shimano MI201Leaded Hub City-Trekking riser bar, 6066 alloy, 40mm rise, swe	Color	Spark blue gloss
Battery Darfon 504Wh, intergrated battery, approved for 'Shimano Service Program', with Smart 2A charger Display Shimano SC-E6100 center mounted LCD display with Bluetooth and ANT private connectivity Fork RST Volant, Lockout, Coil damping, tapered alloy steerer, travel 50mm, QR-axle Samox for Shimano Steps, 38T Chainring Samox for Shimano, Integrated in motor Veedals Wellgo pedals with reflectors Bear Derailleur Shimano Nexus 8 speed Shimano Incer Gear sprocket, 20T Shimano Inner Gear sprocket, 20T Chain KMC E101 EPT Wheelset Shimano Inner Gear sprocket, 20T Chain KMC E101 EPT Wheelset Shimano Marxus 700 cmultichamber alloy rims for disc brakes with 36H spokes, SR 1232K 700c multichamber alloy rims for disc brakes with 36H spokes, SR 232K 700c multichamber alloy rims for disc brakes with 36H strakeset Shimano MT200, 2-piston hydraulic disc, with 180mm front and 160mm rear rotors strakeset Shimano MT200, 2-piston hydraulic disc, with 180mm rise, sweep: 30 degree up, 31.8mm clamp, width in man version: L: 700mm, XL: 720mm / width in lady version: S: 680mm, ML: 700mm sided Selle Italia SS Superflow seatopet Supordia aloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clam	Frame	
Display Shimano SC-E6100 center mounted LCD display with Bluetooth and ANT private connectivity Ork RST Volant, Lockout, Coil damping, tapered alloy steerer, travel 50mm, QR-axle Crankset Samox for Shimano Steps, 38T chaining Obtom Bracket Shimano, integrated in motor Pedals Wellgo pedals with reflectors Stear Derailleur Shimano Nexus 8 speed Shimano Inner Gear sprocket, 20T Shimano Inner Gear sprocket, 20T Chain KMC E101 EPT Vheelset Shimano Maxis Overdrive, 700x47c, Silkshield, 60 TPI wire bread with puncture protection, with reflective stripe Spakes, SP. 122X TOOC multichamber alloy rims for disc brakes with 36H Cries Maxxis Overdrive, 700x47c, Silkshield, 60 TPI wire bread with puncture protection, with reflective stripe Spakestet Shimano MT201 Frists, D346S, 11/8*1.5* headset, angular contact bearings Handlebar Alloy City-Trekking riser bar, 6066 alloy, 40mm rise, sweep: 30 degree up, 31.8mm clamp, width in man version: L: 700mm, XL: 720mm / width in lady version: S: 680mm, ML: 700mm Spides Supersion seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offset Spides Supersion seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offset Steadeleters Alloy extruded fenders, front & rear 3/4 length, stai	Drive Unit	Shimano E-6110 center-motor, 250W rated power, 60Nm of torque, 25km/h maximum assist, for coaster-brake
Fork RST Volant, Lockout, Coil damping, tapered alloy steerer, travel 50mm, QR-axle Samox for Shimano Steps, 38T chainring Sottom Bracket Shimano, integrated in motor Vedals Wellgo pedals with reflectors Rear Derailleur Shimano Nexus 8 speed Shimano Inner Gear sprocket, 20T Chain KMC E101 EPT Vheelset Shimano HB-TX505 front hub, Shimano Nexus 8 speed rear hub, for Center Lock disc and coaster-brake brakes, CN streight stainless steel spokes, SR J32X 700c multichamber alloy rims for disc brakes with 36H Tires Maxxis Overdrive, 700x47c, Silkshield, 60 TPI wire bread with puncture protection, with reflective stripe Strakeset Shimano MT200 Periston MT201 Faskeset First, D346S, 1.1/8"-1.5" headset, angular contact bearings Alloy City-Trekking riser bar, 6066 alloy, 40mm rise, sweep: 30 degree up, 31.8mm clamp, width in man version: L: 700mm, XL: 720mm / width in lady version: S: 680mm, ML: 700mm Stem 3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp, width in man version: L: 700mm, XL: 720mm / width in lady version: S: 680mm, ML: 90mm Strips Comfortable gel grips with padding Suspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offset Strips Suspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offset A	Battery	Darfon 504Wh, intergrated battery, approved for 'Shimano Service Program', with Smart 2A charger
Frankset Samox for Shimano Steps, 38T chainring Sottom Bracket Shimano, integrated in motor Deedals Wellgo pedals with reflectors Rear Derailleur Shimano Nexus 8 speed Shimano Nexus 8 speed Shimano Inter Gear sprocket, 20T Chain KMC E101 EPT Wheelset Shimano HB-TX505 front hub, Shimano Nexus 8 speed rear hub, for Center Lock disc and coaster-brake brakes, CN streight stainless steel spokes, SR J23ZK 700c multichamber alloy rims for disc brakes with 36H Tires Maxxis Overdrive, 700x47c, Silkshield, 60 TPI wire bread with puncture protection, with reflective stripe Brakeset Shimano MT200, 2-piston hydraulic disc, with 180mm front and 160mm rear rotors Strake Levers Shimano MT201 Headset First, D346S, 1.1/8*1.5* headset, angular contact bearings Handlebar Alloy City-Trekking riser bar, 6066 alloy, 40mm rise, sweep: 30 degree up, 31.8mm clamp, width in man version: L: 700mm, XL: 720mm / width in lady version: S: 680mm, M/L: 90mm Sterm 3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp, width in man version: L: 90mm, XL: 110mm / width in lady version: S: 680mm, M/L: 90mm Sterps Comfortable gel grips with padding Saddle Supension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offset Sendereds Alloy extruded fender	Display	Shimano SC-E6100 center mounted LCD display with Bluetooth and ANT private connectivity
Notion Bracket Shimano, integrated in motor Pedals Wellgo pedals with reflectors Rear Derailleur Shimano Nexus 8 speed Shifters Shimano Inner Gear sprocket, 20T Chain KMC E101 EPT Wheelset Shimano MEXUS 8 poed or disc brakes with 36H Shimano MEXUS 022K 700c multichamber alloy rims for disc brakes with 36H Tires Maxis Overdrive, 700x47c, Silkshield, 60 TPI wire bread with puncture protection, with reflective stripe Brakeset Shimano MT200, 2-piston hydraulic disc, with 180mm front and 160mm rear rotors Strake Levers Shimano MT201 Fedads First, D346S, 1.1/8°-1.5" headset, angular contact bearings Handlebar Alloy City-Trekking riser bar, 6066 alloy, 40mm rise, sweep: 30 degree up, 31.8mm clamp, width in man version: L: 700mm, XL: 720mm / width in lady version: S: 680mm, M/L: 700mm Stem 3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp, width in man version: L: 700mm, XL: 110mm / width in lady version: S: 680mm, M/L: 700mm Stem Suppension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offset Setpost Suspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offset Setenders Alloy extruded fenders, front & rear 3/4 length, stainless steel hardware <td>Fork</td> <td>RST Volant, Lockout, Coil damping, tapered alloy steerer, travel 50mm, QR-axle</td>	Fork	RST Volant, Lockout, Coil damping, tapered alloy steerer, travel 50mm, QR-axle
Wellgo pedals with reflectors Rear Derailleur Shimano Nexus 8 speed Shimano Nexus 8 speed Cassette Shimano Inner Gear sprocket, 20T Chain KMC E101 EPT Wheelset Shimano HB-TX505 front hub, Shimano Nexus 8 speed rear hub, for Center Lock disc and coaster-brake brakes, CN streight stainless steel spokes, SR J23ZK 700c multichamber alloy rims for disc brakes with 36H Tires Maxxis Overdrive, 700x47c, Silkshield, 60 TPI wire bread with puncture protection, with reflective stripe Shimano MT200, 2-piston hydraulic disc, with 180mm front and 160mm rear rotors Shake Levers Shimano MT201 Headset First, D346S, 1.1/8*1.5" headset, angular contact bearings Handlebar Alloy City-Trekking riser bar, 6066 alloy, 40mm rise, sweep: 30 degree up, 31.8mm clamp, width in man version: L: 700mm, XL: 720mm / width in lady version: S: 680mm, M/L: 700mm Seifps Comfortable gel grips with padding Gaddle Selle Italia S5 Superflow Seatopst Suspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offset Senders Alloy extruded fenders, front & rear 3/4 length, stainless steel hardware Headlight Lezyne eBike Mini E65, 6-12v, 65 lux, with reflector Taillight Herrmans H-Cargo, 6-12v, with reflector Tubular aluminium carrier, w	Crankset	Samox for Shimano Steps, 38T chainring
Rear Derailleur Shimano Nexus 8 speed Shifters Shimano Nexus 8 speed Cassette Shimano Inner Gear sprocket, 20T Chain KMC E101 EPT Wheelset Shimano HB-TX505 front hub, Shimano Nexus 8 speed rear hub, for Center Lock disc and coaster-brake brakes, CN streight stainless steel spokes, SR J232K 700c multichamber alloy rims for disc brakes with 36H Tires Maxxis Overdrive, 700x47c, Silkshield, 60 TPI wire bread with puncture protection, with reflective stripe Shimano M1200, 2-piston hydraulic disc, with 180mm front and 160mm rear rotors Shake Levers Shimano M1201 Headset First, D346S, 1.1/8"-1.5" headset, angular contact bearings Handlebart Alloy City-Trekking riser bar, 6066 alloy, 40mm rise, sweep: 30 degree up, 31.8mm clamp, width in man version: L: 700mm, XL: 720mm / width in lady version: S: 680mm, M/L: 700mm Steam 3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp, width in man version: L: 90mm, XL: 110mm / width in lady version: S: 680mm, M/L: 90mm Stafps Comfortable gel grips with padding Sele Italia S5 Superflow Supension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offset Alloy extruded fenders, front & rear 3/4 length, stainless steel hardware Headlight Lezyne eBike Mini E65, 6-12v, 65 Lux, with reflector Lezyne eBike Mini E65, 6-12v, 65 Lux, with reflector	Bottom Bracket	Shimano, integrated in motor
Shimano Nexus 8 speed Cassette Shimano Inner Gear sprocket, 20T Chain KMC E101 EPT Wheelset Shimano HB-TX505 front hub, Shimano Nexus 8 speed rear hub, for Center Lock disc and coaster-brake brakes, CN streight stainless steel spokes, SR J23ZK 700c multichamber alloy rims for disc brakes with 36H Tires Maxxis Overdrive, 700x47c, Silkshield, 60 TPI wire bread with puncture protection, with reflective stripe Brakeset Shimano MT200, 2-piston hydraulic disc, with 180mm front and 160mm rear rotors Brake Levers Shimano MT201 Headset First, D346S, 1.1/8"-1.5" headset, angular contact bearings Alloy City-Trekking riser bar, 6066 alloy, 40mm rise, sweep: 30 degree up, 31.8mm clamp, width in man version: L: 700mm, XL: 720mm / width in lady version: S: 680mm, M/L: 700mm Stem 3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp, width in man version: L: 90mm, XL: 110mm / width in lady version: S: 65mm, M/L: 90mm Grade Selle Italia S5 Superflow Steatpost Suspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offset Grades Alloy extruded fenders, front & rear 3/4 length, stainless steel hardware Headlight Lezyne eBike Mini E65, 6-12v, 65 Lvx, with reflector Grades Alloy extruded fenders, front & rear 3/4 length, stainless steel hardware	Pedals	Wellgo pedals with reflectors
CassetteShimano Inner Gear sprocket, 20TChainKMC E101 EPTWheelsetShimano HB-TX505 front hub, Shimano Nexus 8 speed rear hub, for Center Lock disc and coaster-brake brakes, CN streight stainless steel spokes, SR 123ZK 700c multichamber alloy rims for disc brakes with 3GHWreelsetShimano MT200, 2-piston hydraulic disc, with 180mm front and 160mm rear rotorsBrake LeversShimano MT201HeadsetFirst, D346S, 1.1/8"-1.5" headset, angular contact bearingsHandlebarAlloy City-Trekking riser bar, 6066 alloy, 40mm rise, sweep: 30 degree up, 31.8mm clamp, width in man version: L: 700mm, XL: 720mm / width in lady version: S: 680mm, M/L: 700mmStem3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp, width in man version: L: 90mm, XL: 110mm / width in lady version: S: 65mm, M/L: 90mmScipsComfortable gel grips with paddingSeatpostSuspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offsetSeatpostSuspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offsetAlloy extruded fenders, front & rear 3/4 length, stainless steel hardwareHeadlightLezyne eBike Mini E65, 6-12v, 65 lux, with reflectorCarlierTubular aluminium carrier, with Snap-IT platform and spring clamp, H-Cargo rear light mount	Rear Derailleur	Shimano Nexus 8 speed
ChainKMC E101 EPTWheelsetShimano HB-TX505 front hub, Shimano Nexus 8 speed rear hub, for Center Lock disc and coaster-brake brakes, CN streight stainless steel spokes, SR J23ZK 700c multichamber alloy rims for disc brakes with 36H"IrresMaxxis Overdrive, 700x47c, Silkshield, 60 TPI wire bread with puncture protection, with reflective stripeBrakesetShimano MT200, 2-piston hydraulic disc, with 180mm front and 160mm rear rotorsBrake LeversShimano MT201HeadsetFirst, D346S, 1.1/8"-1.5" headset, angular contact bearingsHandlebarAlloy City-Trekking riser bar, 6066 alloy, 40mm rise, sweep: 30 degree up, 31.8mm clamp, width in man version: L: 700mm, XL: 720mm / width in lady version: S: 680mm, M/L: 700mmStem3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp, width in man version: L: 90mm, XL: 110mm / width in lady version: S: 65mm, M/L: 90mmGripsComfortable gel grips with paddingSeaddleSelle Italia S5 SuperflowSeaddleSelle Italia S5 SuperflowSeatpostSuspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offsetendersAlloy extruded fenders, front & rear 3/4 length, stainless steel hardwareHeadlightLezyne eBike Mini E65, 6-12v, 65 lux, with reflectorTaillightHerrmans H-Cargo, 6-12v, with reflectorTubular aluminium carrier, with Snap-IT platform and spring clamp, H-Cargo rear light mount	Shifters	Shimano Nexus 8 speed
WheelsetShimano HB-TX505 front hub, Shimano Nexus 8 speed rear hub, for Center Lock disc and coaster-brake brakes, CN streight stainless steel spokes, SR J23ZK 700c multichamber alloy rims for disc brakes with 36HWineMaxxis Overdrive, 700x47c, Silkshield, 60 TPI wire bread with puncture protection, with reflective stripeBrakesetShimano MT200, 2-piston hydraulic disc, with 180mm front and 160mm rear rotorsBrakesetShimano MT201HeadsetFirst, D346S, 1.1/8"-1.5" headset, angular contact bearingsHandlebarAlloy City-Trekking riser bar, 6066 alloy, 40mm rise, sweep: 30 degree up, 31.8mm clamp, width in man version: L: 700mm, XL: 720mm / width in lady version: S: 680mm, M/L: 700mmSteam3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp, width in man version: L: 90mm, XL: 110mm / width in lady version: S: 65mm, M/L: 90mmGraphComfortable gel grips with paddingSeatpostSuspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offset seatpostGendersAlloy extruded fenders, front & rear 3/4 length, stainless steel hardwareHeadlightLezyne eBike Mini E65, 6-12v, 65 lux, with reflectorTaillightHerrmans H-Cargo, 6-12v, with reflectorCarrierTubular aluminium carrier, with Snap-IT platform and spring clamp, H-Cargo rear light mount	Cassette	Shimano Inner Gear sprocket, 20T
spokes, SR J23ZK 700c multichamber alloy rims for disc brakes with 36HMaxxis Overdrive, 700x47c, Silkshield, 60 TPI wire bread with puncture protection, with reflective stripeBrakesetShimano MT200, 2-piston hydraulic disc, with 180mm front and 160mm rear rotorsBrake LeversShimano MT201HeadsetFirst, D346S, 1.1/8"-1.5" headset, angular contact bearingsHandlebarAlloy City-Trekking riser bar, 6066 alloy, 40mm rise, sweep: 30 degree up, 31.8mm clamp, width in man version: L: 700mm, XL: 720mm / width in lady version: S: 680mm, M/L: 700mmStem3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp, width in man version: L: 90mm, XL: 110mm / width in lady version: S: 65mm, M/L: 90mmGripsComfortable gel grips with paddingGaddleSelle Italia S5 SuperflowGeatpostSuspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offsetHeadlightLezyne eBike Mini E65, 6-12v, 65 lux, with reflectorHeadlightHerrmans H-Cargo, 6-12v, with reflectorTubular aluminium carrier, with Snap-IT platform and spring clamp, H-Cargo rear light mount	Chain	KMC E101 EPT
BrakesetShimano MT200, 2-piston hydraulic disc, with 180mm front and 160mm rear rotorsBrake LeversShimano MT201HeadsetFirst, D346S, 1.1/8"-1.5" headset, angular contact bearingsHandlebarAlloy City-Trekking riser bar, 6066 alloy, 40mm rise, sweep: 30 degree up, 31.8mm clamp, width in man version: L: 700mm, XL: 720mm / width in lady version: S: 680mm, M/L: 700mmStem3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp, width in man version: L: 90mm, XL: 110mm / width in lady version: S: 65mm, M/L: 90mmGripsComfortable gel grips with paddingSaddleSelle Italia S5 SuperflowSeatpostSuspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offsetFendersAlloy extruded fenders, front & rear 3/4 length, stainless steel hardwareHeadlightLezyne eBike Mini E65, 6-12v, 65 lux, with reflectorFaillightHerrmans H-Cargo, 6-12v, with Snap-IT platform and spring clamp, H-Cargo rear light mount	Wheelset	
Brake LeversShimano MT201HeadsetFirst, D346S, 1.1/8"-1.5" headset, angular contact bearingsHandlebarAlloy City-Trekking riser bar, 6066 alloy, 40mm rise, sweep: 30 degree up, 31.8mm clamp, width in man version: L: 700mm, XL: 720mm / width in lady version: S: 680mm, M/L: 700mmStem3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp, width in man version: L: 90mm, XL: 110mm / width in lady version: S: 65mm, M/L: 90mmStripsComfortable gel grips with paddingScaddleSelle Italia S5 SuperflowScatpostSuspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offsetSendersAlloy extruded fenders, front & rear 3/4 length, stainless steel hardwareHeadlightLezyne eBike Mini E65, 6-12v, 65 lux, with reflectorTaillightHerrmans H-Cargo, 6-12v, with reflectorTubular aluminium carrier, with Snap-IT platform and spring clamp, H-Cargo rear light mount	Tires	Maxxis Overdrive, 700x47c, Silkshield, 60 TPI wire bread with puncture protection, with reflective stripe
HeadsetFirst, D346S, 1.1/8"-1.5" headset, angular contact bearingsHeadlebarAlloy City-Trekking riser bar, 6066 alloy, 40mm rise, sweep: 30 degree up, 31.8mm clamp, width in man version: L: 700mm, XL: 720mm / width in lady version: S: 680mm, M/L: 700mmStem3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp, width in man version: L: 90mm, XL: 110mm / width in lady version: S: 65mm, M/L: 90mmStem3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp, width in man version: L: 90mm, XL: 110mm / width in lady version: S: 65mm, M/L: 90mmScienceComfortable gel grips with paddingScaddleSelle Italia S5 SuperflowScatpostSuspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offsetGendersAlloy extruded fenders, front & rear 3/4 length, stainless steel hardwareHeadlightLezyne eBike Mini E65, 6-12v, 65 lux, with reflectorTaillightHerrmans H-Cargo, 6-12v, with reflectorRear CarrierTubular aluminium carrier, with Snap-IT platform and spring clamp, H-Cargo rear light mount	Brakeset	Shimano MT200, 2-piston hydraulic disc, with 180mm front and 160mm rear rotors
HandlebarAlloy City-Trekking riser bar, 6066 alloy, 40mm rise, sweep: 30 degree up, 31.8mm clamp, width in man version: L: 700mm, XL: 720mm / width in lady version: S: 680mm, M/L: 700mmStem3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp, width in man version: L: 90mm, XL: 110mm / width in lady version: S: 65mm, M/L: 90mmGripsComfortable gel grips with paddingSaddleSelle Italia S5 SuperflowSeatpostSuspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offsetFendersAlloy extruded fenders, front & rear 3/4 length, stainless steel hardwareHeadlightLezyne eBike Mini E65, 6-12v, 65 lux, with reflectorGaillightHerrmans H-Cargo, 6-12v, with reflectorRear CarrierTubular aluminium carrier, with Snap-IT platform and spring clamp, H-Cargo rear light mount	Brake Levers	Shimano MT201
Iady version: S: 680mm, M/L: 700mm3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp, width in man version: L: 90mm, XL: 110mm / width in lady version: S: 65mm, M/L: 90mmGripsComfortable gel grips with paddingGaddleSelle Italia S5 SuperflowGeatpostSuspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offsetGendersAlloy extruded fenders, front & rear 3/4 length, stainless steel hardwareHeadlightLezyne eBike Mini E65, 6-12v, 65 lux, with reflectorGaillightHerrmans H-Cargo, 6-12v, with reflectorRear CarrierTubular aluminium carrier, with Snap-IT platform and spring clamp, H-Cargo rear light mount	Headset	First, D346S, 1.1/8"-1.5" headset, angular contact bearings
S: 65mm, M/L: 90mmGripsComfortable gel grips with paddingGaddleSelle Italia S5 SuperflowGeatpostSuspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offsetGendersAlloy extruded fenders, front & rear 3/4 length, stainless steel hardwareHeadlightLezyne eBike Mini E65, 6-12v, 65 lux, with reflectorGear CarrierTubular aluminium carrier, with Snap-IT platform and spring clamp, H-Cargo rear light mount	Handlebar	
SaddleSelle Italia S5 SuperflowSeatpostSuspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offsetFendersAlloy extruded fenders, front & rear 3/4 length, stainless steel hardwareIeadlightLezyne eBike Mini E65, 6-12v, 65 lux, with reflectorFaillightHerrmans H-Cargo, 6-12v, with reflectorRear CarrierTubular aluminium carrier, with Snap-IT platform and spring clamp, H-Cargo rear light mount	Stem	
SeatpostSuspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offsetSendersAlloy extruded fenders, front & rear 3/4 length, stainless steel hardwareIeadlightLezyne eBike Mini E65, 6-12v, 65 lux, with reflectorFaillightHerrmans H-Cargo, 6-12v, with reflectorRear CarrierTubular aluminium carrier, with Snap-IT platform and spring clamp, H-Cargo rear light mount	Grips	Comfortable gel grips with padding
FendersAlloy extruded fenders, front & rear 3/4 length, stainless steel hardwareHeadlightLezyne eBike Mini E65, 6-12v, 65 lux, with reflectorTaillightHerrmans H-Cargo, 6-12v, with reflectorRear CarrierTubular aluminium carrier, with Snap-IT platform and spring clamp, H-Cargo rear light mount	Saddle	Selle Italia S5 Superflow
HeadlightLezyne eBike Mini E65, 6-12v, 65 lux, with reflectorFaillightHerrmans H-Cargo, 6-12v, with reflectorRear CarrierTubular aluminium carrier, with Snap-IT platform and spring clamp, H-Cargo rear light mount	Seatpost	Suspension seatpost with anti-sideplay, 40mm travel, 31.6mm diameter, 12mm offset
FaillightHerrmans H-Cargo, 6-12v, with reflectorRear CarrierTubular aluminium carrier, with Snap-IT platform and spring clamp, H-Cargo rear light mount	enders	Alloy extruded fenders, front & rear 3/4 length, stainless steel hardware
Rear Carrier Tubular aluminium carrier, with Snap-IT platform and spring clamp, H-Cargo rear light mount	Headlight	Lezyne eBike Mini E65, 6-12v, 65 lux, with reflector
	Faillight	Herrmans H-Cargo, 6-12v, with reflector
Adjustable kickstand, Chainguard	Rear Carrier	Tubular aluminium carrier, with Snap-IT platform and spring clamp, H-Cargo rear light mount
	Accessories	Adjustable kickstand, Chainguard