

Step-Over: L (55cm), XL (60cm) / Low-Step: M (50cm), L (55cm) / Step-Through: M (50cm), L (55cm)
Matt gray
BESV premium alloy frame with down tube for integrated Darfon battery, Shimano center-motor with protection cover, tapered 1 1/8" - 1.5" head tube, post disc mount, cold-forged dropout and replaceable hanger
Shimano E-6100 center-motor, 250W rated power, 60Nm of torque, 25km/h maximum assist
Darfon intergrated battery, 504Wh with 4A charger
Shimano E-6100 center mounted LCD display with Bluetooth and ANT private connectivity
RST, Coil damping, tapered alloy steerer, travel 50mm
Shimano E6100, 38T chainring
Shimano, integrated in motor
Wellgo C316DU with reflectors
Shimano Deore 10 speed
Shimano Deore 10 speed
Shimano Tiagra 10 speed, 11-34T
KMC e10 EPT
Shimano M475 front hub and rear hub, for 6-bolt disc brakes, straight stainless steel spokes, 700c multichamber alloy rims for disc brakes with 36H
Schwalbe Energizer Plus Performance, 700x47c, Addix compound, 67 EPI wire bead, with reflective stripe
Shimano MT201, 2-piston hydraulic disc, with 180mm front and 160mm rear rotors
Shimano MT201, 3 finger lever
First Components, 1 1/8" - 1.5" headset, retainer bearings
Alloy City-Trekking, rise bar, 2014 alloy, 20mm rise, sweep: 35° up, 31.8mm clamp, width: 680mm
Alloy City-Trekking, adjustable 0-90°, 31.8mm clamp
Comfortable gel grips with padding
Comfortable saddle with D1 padding
Suspension seatpost, 40mm travel, 31.6mm diameter, 17mm offset
Alloy extruded fenders, front & rear 3/4 length, stainless steel hardware
Herrmans H-BLACK MR4 E-Bike, 120 Lumens, 6-12V, with reflector, stem mounted
Herrmans H-Cargo, 6-12V, with reflector
Integrated with fender, tubular aluminium carrier, with platform and spring clamp, rear light mount
Day light integrated in head tube, adjustable kickstand, chainguard